



HHT2

Hi-Temp R2AT Braided Hose

Abrasion resistant hose for use in high temperature and high pressure hydraulic applications.



TECHNICAL DATA

Specifications	Meets or Exceeds SAE 100R2AT, EN853 2SN
Tube	Blue, oil resistant synthetic rubber
Reinforcement	2 high tensile steel wire braids
Cover	Blue, synthetic rubber resistant to oils, abrasion and weather condition.
Temperature	-40°F to +300°F (-40°C to +135°C)
Industry Approvals	MSHA, ABS, DNV, USCG
Fittings	

Fittings Series	Hose Size					
	04	06	08	10	12	16
F2	✓	✓	✓	✓	✓	✓
F	F2 Fer	F2 Fer	F2 Fer	F2 Fer	F2 Fer	F2 Fer

I.D.			#	O.D.		Working Pressure		Burst Pressure		Bend Radius		Weight	
Dash	Inch	Dn	Part Number	Inch	mm	psi	bar	psi	bar	inch	mm	lbs/ft	Kg/mt
4	1/4	06	HHT2-4	0.59	15.0	5,800	400	23,200	1,600	4	100	0.22	0.33
6	3/8	10	HHT2-6	0.75	19.0	4,800	330	19,200	1,320	5	130	0.35	0.52
8	1/2	12	HHT2-8	0.87	22.0	4,000	275	16,000	1100	7	180	0.43	0.64
12	3/4	19	HHT2-12	1.15	29.2	3,100	215	12,400	860	9.5	240	0.62	0.92
16	1	25	HHT2-16	1.48	37.6	2,400	165	9,600	660	12	300	0.92	1.37